

1 | 2 | 3 | 4 | 5 | 6

产品料号 Part No.	外螺纹规格AG Outside Thread	内螺纹规格LG Inside Thread	外螺纹长度GL Outside thread length	总长L Total length	扳手尺寸SW Wrench size	重量/Weight g
J21030112002	M12*1.5	M16*1.5	8	22	20	3
J21030132002	M16*1.5	M20*1.5	10	27	27	3.2
J21030152002	M20*1.5	M25*1.5	8	25	30	4.6
J21030182002	M25*1.5	M32*1.5	11	30	36	9.1
J21030192002	M32*1.5	M40*1.5	15	34	45	13
J21030202002	M40*1.5	M50*1.5	13	37	55	23

产品料号 Part No.	外螺纹规格AG Outside Thread	内螺纹规格LG Inside Thread	外螺纹长度LG Outside thread length	总长L Total length	扳手尺寸SW Wrench size	重量/Weight g
J21030012002	PG7	PG9	8	20	19	2.8
J21030022002	PG9	PG11	10	24	22	3.2
J21030032002	PG11	PG13.5	8	23	24	3.5
J21030042002	PG13.5	PG16	8	25	27	4.9
J21030052002	PG16	PG21	10	27	30	5.3
J21030062002	PG21	PG29	11	32	42	12.2
J21030072002	PG29	PG36	11	35	52	18
J21030082002	PG36	PG42	13	42	60	26.8
J21030092002	PG42	PG48	15	46	65	29.7



— 材料:

- 主体: 尼龙
- 密封元件: NBR
- 颜色: 灰色
- 温度范围: -40°C ~ 100°C , 短时间可以达到 120°C
- 使用场合: 适用于需要将螺纹直径扩大的场合
- 防护等级: IP68 (在使用O型圈的情况下)

- Material:

- Body: polyamide
- Sealing: NBR
- Colour: grey
- Temperature range: -40°C – 100°C , short-term 120°C
- Applications: apply to the situation of the diameter need to be enlarged
- Degree of protection: IP68(with O-sealing)

A