





- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: -40°C — $+125^{\circ}\text{C}$
- 防护等级: IP65
- 出线方向: 侧出线
- 出线孔数: 2
- 螺纹规格: PG29
- 联锁元件:
 - 锁扣方式: 金属双扣
 - 材料: 不锈钢+橡胶
- 密封元件: NBR

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 7037(gery)
- Temperature range: -40°C – +125°C
- Degree of protection: IP65
- Cable entry: side entry
- No. of cable entries: 2
- Thread size: PG29
- Locking element:
 - Locking type: double locking latch
 - material: stainless steel+TPR
- Hoods/Housings sealing: NBR

						表面处理 Finish		—		图号 Drawing No.		—	
						材料 Material		—		产品代号 Part Code		H32A-SF-2L/SC-2PG29	
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date				产品料号 Part No.		1100322411032	
	姓名/Name	日期/Date			姓名/Name	日期/Date		比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	
绘图 Drawn	SL CHEN	18.10.2010		标准化 Stand.	—	—		1:2	V1.1	435g	—	—	
审核 Checked	P RAO	18.10.2010								All Dimensions in mm Original Size DIN A 4			 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD
工艺 Process	—	—		批准 Approved	YY LIN	18.10.2010							