






技术参数:

- 材料: 压铸锌
- 表面处理: 钝化
- 温度范围: -40°C - $+125^{\circ}\text{C}$
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
 - 锁扣方式: 单扣
 - 材料: 铁镀锌
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: PG11

Technical specification:

- Material: zinc die-cast
- Surface: passivating treatment
- Temperature range: -40°C - $+125^{\circ}\text{C}$
- Degree of protection: IP65
(acc.to IEC 60529 for coupled connector)
- Locking element:
 - Locking type: single locking latch
 - material: steel lever with zinc plated
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: PG11



						表面处理 Finish		—		图号 Drawing No.	—
						材料 Material		—		产品代号 Part Code	EMC.H3A-SF-1L/W-PG11
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale		版本 REV.	重量 Weight	数量 Qty.
绘图 Drawn	BQ LUO	04.17.2018	标准化 Stand.	—	—	—	1:1		V1.2	80g	—
审核 Checked	P RAO	04.17.2018	—	—	—	—	—		—	—	—
工艺 Process	—	—	批准 Approved	YY LIN	04.17.2018	—	—		—	—	—
							All Dimensions in mm Original Size DIN A 4		WAIN 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		