







面板开孔图
Panel cut out



技术参数:

- 材料: 压铸锌
- 表面处理: 钝化
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
 - 锁扣方式: 单扣
 - 材料: 铁镀锌
- 出线方向: 底部出线

Technical specification:

- Material: zinc die-cast
- Surface: passivating treatment
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Degree of protection: IP65
(acc.to IEC 60529 for coupled connector)
- Locking element:
 - Locking type: single locking latch
 - material: steel lever with zinc plated
- Cable entry: bottom entry

						表面处理 Finish	—			图号 Drawing No.	—				
						材料 Material	—			产品代号 Part Code	EMCD.H3A-BK-1L/W-SE				
标记 Mark	处数 Number	变更描述/Description			签名 Signature					日期 Date	产品料号 Part No.	1106039241101			
	姓名/Name	日期/Date		姓名/Name	日期/Date					比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	—
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	—	—					1:1	V1.1	63.1g	—		
审核 Checked	P RAO	18.10.2010													
工艺 Process	—	—	批准 Approved	YY LIN	18.10.2010	 	All Dimensions in mm Original Size DIN A 4			 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD					