





- 材料：压铸铝
- 盖子材料：PC
- 表面处理：粉末喷涂
- 颜色：RAL 7037（灰色）
- 温度范围：-40℃ — +125℃
- 防护等级：IP65（联锁状态, IEC 60529）
- 出线方向：侧出线
- 出线孔数：1
- 螺纹规格：M25
- 联锁元件：
 - 锁扣方式：金属单扣
 - 材料：不锈钢+软胶
- 密封元件：NBR

- Material: aluminium die-cast
- Material,cover: PC
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40°C – $+125^{\circ}\text{C}$
- Degree of protection: IP65
(acc.to IEC 60529 for coupled connector)
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M25
- Locking element:
 - Locking type: single locking latch
 - material: stainless steel+TPR
- Hoods/Housings sealing: NBR

						表面处理 Finish	—			图号 Drawing No.	—
						材料 Material	—			产品代号 Part Code	H6B-SF-1L/SC-CV-M25
标记 Mark	处数 Number	变更描述/Description			签名 Signature					日期 Date	产品料号 Part No.
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	—
绘图 Drawn	SL CHEN	18.10.2010	标准化 Stand.	—	—	1:2	V1.1	240g	—	 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	
审核 Checked	P RAO	18.10.2010									
工艺 Process	—	—	批准 Approved	YY LIN	18.10.2010						