







面板开孔图
Panel cut out



技术参数:

- 材料：压铸铝
- 表面处理：粉末喷涂
- 颜色：RAL 7037（灰色）
- 温度范围：-40℃ - +125℃
- 防护等级：IP65（联锁状态, IEC 60529）
- 出线方向：底部出线
- 联锁元件：
 - 锁扣方式：单扣
 - 材料：不锈钢+橡胶
- 密封元件：NBR

Technical specification:

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40°C - +125°C
- Degree of protection: IP65
(acc.to IEC 60529 for coupled connector)
- Cable entry: bottom entry
- Locking element:
 - Locking type: single locking latch
 - material: stainless steel+TPR
- Hoods/Housings sealing: NBR

						表面处理 Finish	—			图号 Drawing No.	—
						材料 Material	—			产品代号 Part Code	H6B-BK-1L/SC
标记 Mark	处数 Number	变更描述/Description			签名 Signature		日期 Date				产品料号 Part No.
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	—
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	—	—	3:2	V1.1	106g	—		
审核 Checked	P RAO	18.10.2010									
工艺 Process	—	—	批准 Approved	YY LIN	18.10.2010			All Dimensions in mm Original Size DIN A 4			厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD