



- 技术参数:
- 材料: 压铸铝
 - 表面处理: 粉末喷涂
 - 颜色: RAL 7037 (灰色)
 - 温度范围: -40℃ - +125℃
 - 防护等级: IP65 (联锁状态, IEC 60529)
 - 联锁元件:
 - 锁扣方式: 双扣
 - 材料: 不锈钢+软胶
 - 出线方向: 顶出线
 - 出线孔数: 1
 - 螺纹规格: PG29

- Technical specification:
- Material: aluminium die-cast
 - Surface: powder-coated
 - Colour: RAL 7037(grey)
 - Temperature range: -40℃ - +125℃
 - Degree of protection: IP65 (acc.to IEC 60529 for coupled connector)
 - Locking element:
 - Locking type: double locking latch
 - material: stainless steel+TPR
 - Cable entry: top entry
 - No. of cable entries: 1
 - Thread size: PG29



						表面处理 Finish	—	图号 Drawing No.	—
						材料 Material	—	产品代号 Part Code	H16B-TEH-2L/SC-PG29
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date		产品料号 Part No.	1110164415012
绘图 Drawn	姓名/Name	日期/Date	标准化 Stand.	姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.
	ZL CHEN	26.02.2019		—	—	1:2	V1.1	260g	—
	审核 Checked	P RAO	26.02.2019						
工艺 Process	—	—	批准 Approved	HQ ZHANG	26.02.2019			All Dimensions in mm Original Size DIN A 4	
									厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.,LTD