






技术参数:

- 材料: 压铸铝
- 表面处理: 环氧粉末涂料
- 颜色: RAL 9005 (黑色)
- 温度范围: -40°C - $+125^{\circ}\text{C}$
- 防护等级: IP65
- 出线方向: 侧出线
- 出线孔数: 2
- 螺纹规格: 2M20
- 联锁元件:
 - 锁扣方式: 金属单扣
 - 材料: 不锈钢+软胶
- 密封元件: FPM

Technical Specification:

- Material: aluminium die-cast
- Surface: corrosion resistant
- Colour: RAL 9005(black)
- Temperature range: -40°C - $+125^{\circ}\text{C}$
- Degree of protection: IP65
- Cable entry: side entry
- No. of cable entries: 2
- Thread size: 2M20
- Locking element:
 - Locking type: single locking latch
 - material: stainless steel+TPR
- Hoods/Housings sealing: FPM

						表面处理 Finish		—		图号 Drawing No.	—
						材料 Material		—		产品代号 Part Code	H6B-MSFH-1L/SC-2M32
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale		版本 REV.	重量 Weight	数量 Qty.
绘图 Drawn	P YU	08.12.2023	标准化 Stand.	—	—	—	1:2	V1.1	320g	—	—
审核 Checked	Q GAO	08.12.2023	—	—	—	—	—	—	—	—	—
工艺 Process	—	—	批准 Approved	HQ ZHANG	08.12.2023	—	—	—	—	—	—
All Dimensions in mm Original Size DIN A 4										WAIN 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	