





选配件/Apolegamy

产品代号/Part Code	产品料号/Part No.	备注/Remark
HEB/P-1T2	1980020070027	横向2Pin短接/Horizontal 2Pin short circuit
HEB/P-1T3	1980020070028	横向3Pin短接/Horizontal 3Pin short circuit
HEB/P-2T1	1980020070029	纵向2Pin短接/Longitudinal 2Pin short circuit



技术参数:

插芯:

- 插针数: 6+PE
- 额定电流: 16A
- 额定电压: 500V
- 额定脉冲电压: 6kV
- 污染等级: 3
- 依据UL/CSA的额定电压: 600V
- 绝缘阻抗: $\geq 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: -40℃ ~ +125℃
- 依据UL 94的阻燃等级: V0
- 可插拔次数: ≥ 500
- 可实现短接功能 (选配)

插针:

- 接线方式: 弹片连接
- 材料: 铜合金
- 表面处理: 镀银
- 接触电阻: $\leq 3m\Omega$
- 线径范围: 0.5-4mm² (20-12 AWG)
- (带管形接线端子线径范围: 0.14-2.5mm²/26-14 AWG)
- 剥线长度: 9.5mm

Technical specification:

Insiders:

- No. of contact: 6+PE
- Rated current: 16A
- Rated voltage: 500V
- Rated impulse voltage: 6kV
- Pollution degree: 3
- Rated voltage acc.to UL/CSA: 600V
- Insulation resistance: $\geq 10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: -40℃ ~ +125℃
- Flammability acc.to UL 94: V0
- Mating cycles: ≥ 500
- Can realize short circuit function (optional)

Contacts:

- Terminal: spring terminal
- Material: copper alloy
- Surface: hard-silver plated
- Contact resistance: $\leq 3m\Omega$
- Wire gauge: 0.5-4mm² (20-12 AWG)
- (For wires with crimped female, wire gauge: 0.14-2.5mm²/26-14 AWG)
- Stripping length: 9.5mm

						表面处理 Finish				—				图号 Drawing No.		DW2022083-107	
						材料 Material				—				产品代号 Part Code		HE-006-MQ P	
标记 Mark	失效 Number	变更描述/Description			签名 Signature	日期 Date						产品料号 Part No.				1220000990500	
	姓名/Name	日期/Date			姓名/Name	日期/Date		比例 Scale	版本 REV.	重量 Weight	数量 Qty.			产品名称 Part Name		HE-006-MQ P,成品	
绘图 Drawn	ZY YE	2023-2-3		标准化 Stand.	—	—		1:1	01	39.5g	—						
审核 Checked	HZ LAN	2023-2-3															
工艺 Process	—	—		批准 Approved	HQ ZHANG	2023-2-3				All Dimensions in mm Original Size DIN A 4				 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD			