



技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: PG29
- 联锁元件:
 - 锁扣方式: 金属单扣
 - 材料: 不锈钢+软胶
- 密封元件: NBR

Technical Specification:

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40℃ - +125℃
- Degree of protection: IP65
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: PG29
- Locking element:
 - Locking type: single locking latch
 - material: stainless steel+TPR
- Hoods/Housings sealing: NBR

				表面处理 Finish				-		图号 Drawing No.		-	
				材料 Material				-		产品代号 Part Code		HV24B-SFH-1L/SC-PG29	
标记 Mark		处数 Number		变更描述/Description				签名 Signature		日期 Date		产品料号 Part No.	
				姓名/Name		日期/Date		姓名/Name		日期/Date		1240242215012	
绘图 Drawn		JY ZENG		10.01.2024		标准化 Stand.		-		-		产品名称 Part Name	
审核 Checked		Q GAO		10.01.2024								-	
工艺 Process		-		-		批准 Approved		HQ ZHANG		10.01.2024		-	
				比例 Scale				1:2		版本 REV.		V1.1	
				重量 Weight				500g		数量 Qty.		-	
				All Dimensions in mm Original Size DIN A 4						厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD			