






技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP67 (联锁状态,IEC 60529)
- 联锁元件:
 - 锁扣方式:金属双扣
 - 材料:不锈钢+软胶
- 出线方向:侧出线
- 出线孔数: 1
- 螺纹规格: M20

Technical specification:

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40℃ - +125℃
- Degree of protection: IP67
(acc.to IEC 60529 for coupled connector)
- Locking element:
 - Locking type: double locking latch
 - material: stainless steel+TPR
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M20

						表面处理 Finish	—				图号 Drawing No.	—
						材料 Material	—				产品代号 Part Code	WV10B-SE-2L/SC-M20
标记 Mark	处数 Number	变更描述/Description			签名 Signature		日期 Date					产品料号 Part No.
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name		
绘图 Drawn	GY HUANG	02.12.2023	标准化 Stand.	—	—	2:3	V1.1	210g	—	—		
审核 Checked	Q GAO	02.12.2023				 	All Dimensions in mm Original Size DIN A 4				 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	
工艺 Process	—	—	批准 Approved	HQ ZHANG	02.12.2023							