



- Terminal: axial screw terminal
- Material: copper alloy
- Surface: hard-silver plated
- Contact resistance: $\leq 0.2\text{m}\Omega$
- For stranded wire acc. to: IEC 60 228-5
- Wire gauge:
 - Power contacts: 35-70mm²(2-00 AWG)
 - PE contacts: 16-35mm²(5-2 AWG)
- Hexagonal driver:
 - Power contacts: SW5
 - PE contacts: SW4
- Stripping length:
 - Power contacts: 22mm
 - PE contacts: 14mm
- Tightening torque:
 - Power contacts:

mm ² :	35	50	70
N•m:	8	9	10
 - PE contacts: 6N•m

						表面处理 Finish		—		图号 Drawing No.		—											
						材料 Material		—		产品代号 Part Code		HK-003/0-M											
标记 Mark		处数 Number		变更描述/Description						签名 Signature		日期 Date		产品料号 Part No.		1280030110001							
		姓名/Name		日期/Date						姓名/Name		日期/Date		比例 Scale		版本 REV.		重量 Weight		数量 Qty.		产品名称 Part Name	
绘图 Drawn		BQ LUO		18.10.2010		标准化 Stand.		—		—		—		1:2		V1.0		286.43g		—		—	
审核 Checked		P RAO		18.10.2010																			
工艺 Process		—		—		批准 Approved		YY LIN		18.10.2010		 		All Dimensions in mm Original Size DIN A 4				厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD					