






技术参数:

- 模块数量: 4
- 接地线:
 - 功率线: 4-10mm²(12-8 AWG)
 - 信号线: 1-2.5mm²(18-14 AWG)
- 材料: 压铸铝
- 温度范围: -40℃ - +125℃
- 可插拔次数: ≥500

Technical specification:

- No. of module: 4
- Wire gauge(PE contact):
 - Power side: 4-10mm²(12-8 AWG)
 - Signal side: 1-2.5mm²(18-14 AWG)
- Material: zinc die-cast
- Temperature range: -40℃ - +125℃
- Mating cycles: ≥500

						表面处理 Finish	—	图号 Drawing No.	—
						材料 Material	—	产品代号 Part Code	HF16B-NLA3
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date		产品料号 Part No.	1290160001003
		姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight
绘图 Drawn		ZL CHEN	14.01.2019	标准化 Stand.	—	—	1:1	V1.2	84g
审核 Checked		P RAO	14.01.2019						数量 Qty.
工艺 Process		—	—	批准 Approved	HQ ZHANG	14.01.2019			—
							⌀	≡	All Dimensions in mm Original Size DIN A 4
									厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD