





日期/Date		Filing Clerk		1		2		3		4		5		6															
技术参数: - 产品系列: M12 A-code - 插针数: 3 - 额定电流(40℃): 4A - 额定电压: 250V - 额定脉冲电压: 2500V - 污染等级: 3 - 接触电阻: ≤10mΩ - 绝缘电阻: ≥100MΩ - 锁紧方式: 螺纹式M12*1 - 电缆类型: PUR, 黑色RAL9005 - 线规: 0.34mm ² (AWG22) - 防护等级: IP67 - 插拔次数: ≥100 - 温度范围: -25℃ ... +85℃ - 锁紧螺帽: 不锈钢 - 外壳材料: TPU - 插体材料: PA - 插针材料: 铜合金 - 插针电镀材料: 金										插针数 Contacts		料号 Order No.		产品代号 Part Code		电缆长度(L) Cable length		重量 Weight											
										3		1630034014241		M12S-M03A-T-1.5-PUR		1.5m		68g											
												1630034014242		M12S-M03A-T-5.0-PUR		5m		195g											
												-		M12S-M03A-T-L-PUR		Lm		-g											
																													
Technical specification: - Series: M12 A-Code - Number of contacts: 3 - Rated current (40℃): 4A - Rated voltage: 250V - Rated impulse voltage: 2500V - Pollution degree: 3 - Contact resistance: ≤10mΩ - Insulation resistance: ≥100MΩ - Connector locking system: screw M12*1 - Cable type: PUR , Black RAL 9005 - Wire gauge: 0.34mm ² (AWG22) - Degree of protection: IP67 - Mating cycles: ≥100 - Temperature range: -25℃ ... +85℃ - Material of locking system: Stainless steel - Material of housing: TPU - Material of insert: PA - Material of contact: copper alloy - Contact plating: Au										例如型号”M12S-M03A-T-L-PUR”, ”L”表示带线长度, 单位m。 Ex: Part code ”M12S-M03A-T-L-PUR”, the ”L” represents the cable length, unit m.																			
										针位图 Contact arrangements				接线图 Circuit diagram															
																													
										表面处理 Finish		-		图号 Drawing No.		-													
										材料 Material		-		产品代号 Part Code		M12S-M03A-T-L-PUR													
标记 Mark										处数 Number		变更描述/Description		签名 Signature		日期 Date		产品料号 Part No.		-									
绘图 Drawn										姓名/Name		日期/Date		姓名/Name		日期/Date		比例 Scale		版本 REV.		重量 Weight		数量 Qty.		产品名称 Part Name		-	
审核 Checked										L CHEN		13.12.2023		-		-		1:1		V1.1		-g		-		-			
工艺 Process										-		-		批准 Approved		HQ ZHANG		13.12.2023				All Dimensions in mm Original Size DIN A 4				厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD			
1		2		3		4		5		6																			