

日期/Date		档案员 Filing Clerk		1		2		3		4		5		6			
技术参数: - 产品系列: M17 - 插针数: 7(6+PE) - 插针直径(mm): $\phi 1$ - 接线范围(mm²/AWG): 0.03-1.5/AWG32-16 - 接线方式: 冷压连接 - 额定电流(25℃): 14A - 额定电压: 630V - 额定脉冲电压: 6KV - 过电压保护等级: III - 污染等级: 3 - 插针需单独订购。 机械参数: - 外壳材质: 铜合金, 锌合金 - 外壳表面处理: 镀镍 - 插芯材质: PBT - 密封材质: 氟橡胶 - 温度范围: -40℃...+130℃ - 电缆直径: 6-12mm 屏蔽 - 插拔次数: >500 - 防护等级: IP67 Technical specification: - Series: M17 - Number of contacts: 7(6+PE) - Contact diameter(mm): $\phi 1$ - Wire gauge(mm²/AWG): 0.03-1.5/AWG32-16 - Terminal: Crimp - Rated current(25℃): 14A - Rated voltage: 630V - Rated impulse voltage: 6KV - Overvoltage category: III - Pollution degree: 3 Mechanical specification: - Material of housing: CuZn,Zinc(GD-Zn) - Finish of housing:Nickel-plated - Material of Insert:PBT - Material of sealing:FPM - Temperature range: -40℃...+130℃ - Cable Outlet: 6-12mm Shielded - Mating cycles: >500 - Degree of protection: IP67 - Contact need to be ordered separately.						插针数 Contacts		电缆出口直径 ϕ Cable outlet		产品料号 Cable outlet		型号 Part Code		重量 Weight		针位排布图 Contact arrangement	
						7(6+PE)		6-9.5mm		1650077002500		M17-007-CCT/R-D9.5-SH		67.2g			
		9.5-12 mm		1650077002502		M17-007-CCT/R-D12-SH		64.7g									
												比例 Scale: 2:1					
						面板安装开孔图 Panel cut out											