

日期/Date		图例		1		2		3		4		5		6											
技术参数:						插针数 Contacts		电缆出口直径φD Cable outlet		产品料号 Cable outlet		型号 Part Code		重量 Weight											
- 产品系列: M17 - 插针数: 17 - 接线范围(mm²/AWG): 0.14–0.5/AWG26–20 - 接线方式: 冷压连接 - 额定电流(25℃): 3.6A - 额定电压: 63V - 额定脉冲电压: 1.5KV - 过电压保护等级: III - 污染等级: 3 - 插针需单独订购。						17		3–6mm		–		M17–MC017–CCT/R–D6–SH		54.5g											
								6–9.5mm		1650174102501		M17–MC017–CCT/R–D9.5–SH		53.8g											
								9.5–12 mm		1650174102502		M17–MC017–CCT/R–D12–SH		53.2g											
机械参数:						面板安装开孔图 Panel cut out																			
- 外壳材质: 铜合金, 锌合金 - 外壳表面处理: 镀镍 - 插芯材质: PBT - 密封材质: 氟橡胶 - 温度范围: –40℃...+130℃ - 电缆直径: φ3–12mm 屏蔽 - 插拔次数: >500 - 防护等级: IP67																									
Technical specification:						针位排布图 Contact arrangement																			
- Series: M17 - Number of contacts: 17 - Wire gauge(mm²/AWG): 0.14–0.5/AWG26–20 - Terminal: Crimp - Rated current(25℃): 3.6A - Rated voltage: 63V - Rated impulse voltage: 1.5KV - Overvoltage category: III - Pollution degree: 3						正面视图 Front					背面视图 Back view														
						比例 Scale: 2:1					比例 Scale: 2:1														
Mechanical specification:						图号 Drawing No. –																			
- Material of housing: CuZn,Zinc(GD–Zn) - Finish of housing:Nickel–plated - Material of Insert:PBT - Material of sealing:FPM - Temperature range: –40℃...+130℃ - Cable Outlet: φ3–12mm Shielded - Mating cycles: >500 - Degree of protection: IP67 - Contact need to be ordered separately.						表面处理 Finish –					产品代号 Part Code M17–MC017–CCT/R–Dxx–SH														
						材料 Material –					产品料号 Part No. –														
						比例 Scale 1:1					版本 REV. V1.0					重量 Weight –					数量 Qty. –				
工艺 Process –						批准 Approved HQ ZHANG 15.12.2023					All Dimensions in mm Original Size DIN A 4										厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD				