

日期/Date		Filing Clerk		1		2		3		4		5		6					
技术参数: - 产品系列: 7/8 - 插针数: 4(3+PE) - 插针分布: 3+PE - 插针直径(mm): $\varnothing 1.95$ - 接线范围(mm²/AWG): Max1.5mm²/AWG16 - 接线方式: 螺钉连接 - 额定电流(40℃): 9A - 额定电压: 300V - 额定脉冲电压: 4KV - 过电压保护等级: III - 污染等级: 3 机械参数: - 外壳材质: 铜合金,PA - 外壳表面处理: 镀镍 - 插芯材质: TPU、PA - 密封材质: 氟橡胶 - 温度范围: -25℃...+85℃ - 电缆直径: $\varnothing 6-12\text{mm}$ - 插拔次数: >100 - 防护等级: IP67 Technical specification: - Series: 7/8 - Number of contacts: 4(3+PE) - Contact arrangement: 3+PE - Contact diameter(mm): $\varnothing 1.95$ - Wire gauge(mm²/AWG): Max1.5mm²/AWG16 - Terminal: Screw - Rated current(40℃): 9A - Rated voltage: 300V - Rated impulse voltage: 4KV - Overvoltage category: III - Pollution degree: 3 Mechanical specification: - Material of housing: CuZn,PA - Finish of housing: Nickel-plated - Material of Insert: TPU、PA - Material of sealing: FPM - Temperature range: -25℃...+85℃ - Cable Outlet: $\varnothing 6-12\text{mm}$ - Mating cycles: >100 - Degree of protection: IP67						插针数 Contacts		电缆出口直径 $\varnothing$ Cable outlet		产品料号 Cable outlet		型号 Part Code		重量 Weight		针位图 Contact arrangements			
						4(3+PE)		6-8 mm		1680045213001		7/8-F04-S-D8		50g					
								8-10 mm		1680045213002		7/8-F04-S-D10		50g					
								10-12 mm		1680045213003		7/8-F04-S-D12		50g					
												图号 Drawing No.				-			
												产品代号 Part Code				7/8-F04-S-DX			
标记 Mark						处数 Number		变更描述/Description		签名 Signature		日期 Date		材料 Material		产品料号 Part No.		-	
姓名/Name						日期/Date		姓名/Name		日期/Date		比例 Scale		版本 REV.		重量 Weight		数量 Qty.	
绘图 Drawn						TC CHEN		26.12.2023		标准化 Stand.		-		-		1:1		V1.1	
审核 Checked						ZQ XU		26.12.2023											
工艺 Process						-		-		批准 Approved		HQ ZHANG		26.12.2023					
																All Dimensions in mm Original Size DIN A 4			
																		厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.,LTD	