

技术参数:


- 插针数: 12
- 额定电流
信号针: 7A
- 额定电压: 25V~/60V-
- 额定脉冲电压: 1.5KV
- 污染等级: 3
- 绝缘电阻: $\geq 10^{12}\Omega$
- 温度范围: $-40^{\circ}\text{C} \dots +130^{\circ}\text{C}$
- 阻燃等级: V0 (UL94)
- 接触电阻: $\leq 5\text{m}\Omega$
- 插拔次数: ≥ 100
- 插体材料: PBT
- 接线方式: 冷压连接
- 导线截面规格:
-D-Sub区: $0.09-0.82\text{mm}^2(28-18\text{AWG})$

须单独订购冷压针

Technical specification:



- Number of contacts: 12
- Rated current
signal contact: 7A
- Rated voltage: 25V~/60V-
- Rated impulse voltage: 1.5KV
- Pollution degree: 3
- Insulation resistance: $\geq 10^{12}\Omega$
- Temperature range: $-40^{\circ}\text{C} \dots +130^{\circ}\text{C}$
- Flammability acc.to UL94: V0 (UL94)
- Contact resistance: $\leq 5\text{m}\Omega$
- Mating cycles: ≥ 100
- Material of insert: PBT
- Terminal: Crimp termination
- Wire gauge:
-D-Sub contact: $0.09-0.82\text{mm}^2(28-18\text{AWG})$

Order crimp contacts separately



触点排列: 配合面

Contact arrangement: mating side



						表面处理 Finish		—		图号 Drawing No.	—
						材料 Material		—		产品代号 Part Code	HR23-012-FC
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale		版本 REV.	重量 Weight	数量 Qty.
绘图 Drawn	TC CHEN	04.05.2016	标准化 Stand.	—	—	—	2:1	V1.1	2.7g	—	—
审核 Checked	ZM LIN	04.05.2016	—	—	—	—	—	—	—	—	—
工艺 Process	—	—	批准 Approved	YY LUO	04.05.2016	—	—	—	—	—	—
All Dimensions in mm Original Size DIN A 4										WAIN 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.,LTD	