日期/Date	档案员 Filing Clerk







产品料号 Part No.	产品代号 Part Code	颜色 Colour
1370150200002	HCM-015-FC.BK	RAL9005(黑色BLACK)
1370150200003	HCM-015-FC.WH	RAL9003(白色WHITE)
1370150200004	HCM-015-FC.GY	RAL7032(灰色GREY)
1370150200005	HCM-015-FC.BU	RAL5012(蓝色BLUE)

技术参数:
插芯:
- 插针数: 15
- 额定电流: 5A
- 额定电压: 50V
- 额定脉冲电压: 0.8kV
- 污染等级: 3
- 绝缘阻抗: ⩾$10^{10}\Omega$
- 材料: 聚碳酸酯
- 温度范围: −40℃ − +85℃
- 依据UL 94的阻燃等级: V0
- 可插拔次数: ⩾50

插针:
- 接线方式: 冷压连接
- 材料: 铜合金
- 表面处理:
  - ·镀银
  - ·镀金
- 接触电阻: ⩽3mΩ
- 线径范围: 0.09−0.82mm^2(28−18 AWG)
- 工具:
  - ·冷压钳: TL03
  - ·退针器: TL08
- 附件:
  - ·编码元件: CODE-Q3

Technical specification:
Insters:
- No. of contact: 15
- Rated current: 5A
- Rated voltage: 50V
- Rated impulse voltage: 0.8kV
- Pollution degree: 3
- Insulation resistance: ⩾$10^{10}\Omega$
- Material: polycarbonate
- Temperature range: −40℃ − +85℃
- Flammability acc.to UL 94: V0
- Mating cycles: ⩾50

Contacts:
- Terminal: crimp terminal
- Material: copper alloy
- Surface:
  - ·Hard-silver plated
  - ·Hard-gold plated
- Contact resistance: ⩽3mΩ
- Wire gauge: 0.09−0.82mm^2(28−18 AWG)
- Tools:
  - ·Crimp contact tool: TL03
  - ·Contact removal tool: TL08
- Tools:
  - · Coding element: CODE-Q3



标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date
	姓名/Name	日期/Date		姓名/Name	日期/Date
绘图 Drawn	TC YE	05.01.2022	标准化 Stand.	–	–
审核 Checked	HZ LAN	05.01.2022			
工艺 Process	–	–	批准 Approved	HQ ZHANG	05.01.2022

表面处理 Finish	–			图号 Drawing No.	–
材料 Material	–			产品代号 Part Code	–
				产品料号 Part No.	–
比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	–
1:1	V1.0	–	–		
		All Dimensions in mm Original Size DIN A 4		厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	